

UNIFY Identity Broker for Microsoft FIM v3.0.0 Configuration Guide

Installation Notes

- Run the MSI.
- The installer for the adapter defaults to the UNIFY Solutions/Microsoft.FIM directory, and contains a single **Unify.Framework.ILM2007FP1Adapter.dll** file.
- For an ILM2007 instance, this file must be placed in the Microsoft Identity Integration Server/Extensions directory. The **miisserver.exe.config** file in the bin directory of ILM must also be configured with the correct WCF endpoint information. Here is an example of what the file should look like:

```
<?xml version="1.0" encoding="UTF-16"?>
<configuration>
<startup>
<requiredRuntime version="v2.0.50727">
</requiredRuntime>
<supportedRuntime version="v2.0.50727">
</supportedRuntime>
</startup>
<system.serviceModel>
  <bindings>
    <basicHttpBinding>
      <binding name="MetadataExchangeHttpBinding_ILDIFAdapter"
        maxBufferSize="65536" transferMode="Streamed"
        maxReceivedMessageSize="204003200"
        receiveTimeout="10:00:00" closeTimeout="10:00:00"
        openTimeout="10:00:00" sendTimeout="10:00:00">
        <!-- Uncomment the following lines if you wish to use SSL. The
        service config must also be set to use SSL! -->
        <!--
        <security mode="Transport">
          <transport clientCredentialType="None"
            proxyCredentialType="None" realm="">
            <extendedProtectionPolicy policyEnforcement="Never" />
          </transport>
        </security>
        -->
      </binding >
    </basicHttpBinding>
  </bindings>
  <client>
    <endpoint
      binding="basicHttpBinding"
      bindingConfiguration="MetadataExchangeHttpBinding_ILDIFAdapter"
      contract="Unify.Framework.ILDIFAdapter"
```

```
        name="ILDIFAdapter" />
    </client>
</system.serviceModel></configuration>
```

- After this, the MIIIS service must be restarted.